Translated from Italian to English - www.onlinedoctranslator.com

multi plus combinations 2-14

COOLING	INTERNAL UNIT						CAPACITY (KW)				
	Unit A	Unit B	Unit C	Unit D	Unit E	TOTAL UNIT'	Unit A	Unit B	Unit C	Unit D	Unit E
	9					9	2.60				
	12					12	3.50				
	9	9				18	2.13	2.13			
	9	12				21	1.97	2.63			
HEATING	**INTERNAL UNIT**						**CAPACITY (KW)**				
	Unit A	Unit B	Unit C	Unit D	Unit E	TOTAL UNIT'	Unit A	Unit B	Unit C	Unit D	Unit E
	9					9	2.76				
	12					12	3.72				
	9	9				18	2.26	2.26			
	9	12				21	2.10	2.79			

multi plus combinations 2-18

COOLING	INTERNAL UNIT						CAPACITY (KW)				
	Unit A	Unit B	Unit C	Unit D	Unit E	TOTAL UNIT'	Unit A	Unit B	Unit C	Unit D	Unit E
	9					9	2.60				
	12					12	3.20				
	9	9				18	2.55	2.55			
	9	12				21	2.23	2.97			
	12	12				24	2.65	2.65			
	9	18				27	1.80	3.60			
HEATING	**INTERNAL UNIT**						**CAPACITY (KW)**				
	Unit A	Unit B	Unit C	Unit D	Unit E	TOTAL UNIT'	Unit A	Unit B	Unit C	Unit D	Unit E
	9					9	2.65				
	12					12	3.23				
	9	9				18	2.60	2.60			
	9	12				21	2.26	3.01			
	12	12				24	2.68	2.68			
	9	18				27	1.89	3.79			

The specifications in this catalog are subject to change without notice in order for ARYA to bring the latest innovations to its customers. ARYA assumes no responsibility for any errors or omissions.
omissions in this catalog.

ABBINAMENTI multi plus combinations 2-14

TOTAL CATACITY (KW)			TOTAL POWER ABSORBED (KW)			TOTAL ABSORPTION (A)230V			SEER	CLASS ENERGY	EER
Min.	Nom.	Max	Min.	Nom.	Max	Min.	Nom.	Max			
1.00	2.60	3.00	0.22	0.76	0.80	1.06	3.86	4.10	6.1	A++	3.41
1.00	3.50	4.13	0.22	1.04	1.25	1.06	5.28	6.41	6.1	A++	3.35
1.25	4.25	4.95	0.28	1.27	1.61	1.34	6.42	8.26	6.2	A++	3.35
1.25	4.60	5.12	0.28	1.35	1.72	1.34	6.83	8.82	6.2	A++	3.41
TOTAL CATACITY (KW)			TOTAL POWER ABSORBED (KW)			TOTAL ABSORPTION (A)230V			SCOP	CLASS ENERGY	COP
Min.	Nom.	Max	Min.	Nom.	Max	Min.	Nom.	Max			
1.10	2.76	3.02	0.20	0.73	0.79	0.96	3.72	4.05	4.2	A+	3.78
1.10	3.72	3.95	0.20	0.99	1.15	0.96	5.04	5.90	4.2	A+	3.76
1.30	4.51	5.40	0.25	1.19	1.60	1.20	6.06	8.21	4.0	A+	3.79
1.30	4.89	5.69	0.25	1.29	1.69	1.20	6.57	8.67	4.0	A+	3.79

ABBINAMENTI multi plus combinations 2-18

TOTAL CATACITY (KW)			TOTAL POWER ABSORBED (KW)			TOTAL ABSORPTION (A)230V			SEER	CLASS ENERGY	EER
Min.	Nom.	Max	Min.	Nom.	Max	Min.	Nom.	Max			
1.20	2.60	3.00	0.25	0.78	0.88	1.16	3.77	4.50	6.10	A++	3.33
1.20	3.20	3.80	0.25	0.95	1.10	1.16	4.60	5.63	6.10	A++	3.37
1.23	5.10	5.60	0.28	1.55	2.05	1.30	7.50	10.50	6.10	A++	3.29
1.23	5.20	5.80	0.28	1.58	2.05	1.30	7.65	10.50	6.10	A++	3.29
1.95	5.30	5.90	0.30	1.61	2.25	1.39	7.79	11.51	6.10	A++	3.29
2.05	5.40	6.20	0.35	1.67	2.35	1.63	8.08	12.02	6.10	A++	3.23
TOTAL CATACITY (KW)			TOTAL POWER ABSORBED (KW)			TOTAL ABSORPTION (A)230V			SCOP	CLASS ENERGY	COP
Min.	Nom.	Max	Min.	Nom.	Max	Min.	Nom.	Max			
1.20	2.64	3.30	0.20	0.69	0.85	0.96	3.22	4.35	4.00	A+	3.83
1.20	3.23	4.18	0.20	0.85	0.93	0.96	3.96	4.76	4.00	A+	3.80
1.29	5.20	5.75	0.25	1.33	2.05	1.20	6.20	10.50	4.00	A+	3.91
1.29	5.27	5.85	0.25	1.38	2.05	1.20	6.43	10.50	4.00	A+	3.82
1.95	5.36	5.90	0.35	1.43	2.15	1.68	6.67	11.00	4.00	A+	3.75
2.10	5.68	6.30	0.50	1.53	2.20	2.40	7.06	11.25	4.00	A+	3.71

The specifications in this catalog are subject to change without notice so that ARYA can bring the latest innovations to its customers. ARYA assumes no responsibility for any errors or omissions in this catalog.

multi plus combinations 3-21

	INTERNAL UNIT						CAPACITY (KW)				
	Unit A	Unit B	Unit C	Unit D	Unit E	TOTAL UNIT'	Unit A	Unit B	Unit C	Unit D	Unit E
COOLING	9	9				18	2.52	2.52			
	9	12				21	2.58	3.45			
	9	18				27	2.15	4.30			
	12	12				24	3.15	3.15			
	12	18				30	2.62	3.94			
	9	9	9			27	2.15	2.15	2.15		
	9	9	12			30	2.00	2.00	2.67		
	INTERNAL UNIT						CAPACITY (KW)				
	Unit A	Unit B	Unit C	Unit D	Unit E	TOTAL UNIT'	Unit A	Unit B	Unit C	Unit D	Unit E
HEATING	9	9				18	2.84	2.84			
	9	12				21	2.66	3.54			
	9	18				27	2.20	4.41			
	12	12				24	3.30	3.30			
	12	18				30	2.66	3.98			
	9	9	9			27	2.35	2.35	2.35		
	9	9	12			30	2.12	2.12	2.82		

The specifications in this catalog are subject to change without notice in order for ARYA to bring the latest innovations to its customers. ARYA assumes no responsibility for any errors or omissions.
omissions in this catalog.

ABBINAMENTI Multi plus combinations 3-21

TOTAL CATACITY (KW)			TOTAL POWER ABSORBED (KW)			TOTAL ABSORPTION (A)230V			SEER	CLASS ENERGY	EER
Min.	Nom.	Max	Min.	Nom.	Max	Min.	Nom.	Max			
2.80	5.03	5.70	0.34	1.53	2.49	1.50	7.81	12.74	6.10	A++	3.29
2.80	6.03	6.60	0.34	1.85	2.60	1.50	9.44	1.30pm	6.10	A++	3.26
3.00	6.45	6.60	0.36	1.98	2.60	1.59	10.11	1.30pm	6.10	A++	3.26
2.80	6.30	6.60	0.34	1.93	2.60	1.50	9.85	1.30pm	6.10	A++	3.26
3.00	6.56	6.90	0.36	2.01	2.60	1.59	10.26	1.30pm	6.10	A++	3.26
3.00	6.45	6.60	0.36	1.98	2.58	1.59	10.11	13.20	6.10	A++	3.26
3.00	6.67	6.90	0.36	2.05	2.60	1.59	10.46	1.30pm	6.10	A++	3.25
TOTAL CATACITY (KW)			TOTAL POWER ABSORBED (KW)			TOTAL ABSORPTION (A)230V			SCOP	CLASS ENERGY	COP
Min.	Nom.	Max	Min.	Nom.	Max	Min.	Nom.	Max			
2.30	5.67	6.12	0.40	1.53	2.13	1.70	7.86	10.90	4.00	A+	3.71
2.45	6.20	6.55	0.40	1.65	2.53	1.70	8.48	12.94	4.00	A+	3.76
2.45	6.61	6.83	0.40	1.75	2.53	1.70	9.00	12.94	4.00	A+	3.77
2.45	6.59	6.83	0.40	1.72	2.55	1.70	8.84	13.05	4.00	A+	3.83
2.45	6.64	6.83	0.40	1.79	2.55	1.70	9.20	13.05	4.00	A+	3.71
2.45	7.06	7.20	0.42	1.83	2.76	1.79	9.40	14.12	4.00	A+	3.86
2.45	7.06	7.20	0.42	1.86	2.76	1.79	9.55	14.12	4.00	A+	3.80

The specifications in this catalog are subject to change without notice so that ARYA can bring the latest innovations to its customers. ARYA assumes no responsibility for any errors or omissions in this catalog.

multi plus combinations 3-27

	INTERNAL UNIT						CAPACITY (KW)				
	Unit A	Unit B	Unit C	Unit D	Unit E	TOTAL UNIT'	Unit A	Unit B	Unit C	Unit D	Unit E
COOLING	9	9				18	2.80	2.80			
	9	12				21	2.74	3.66			
	12	12				24	3.50	3.50			
	9	18				27	2.53	5.07			
	12	18				30	3.04	4.56			
	18	18				36	3.95	3.95			
	9	9	9			27	2.63	2.63	2.63		
	9	9	12			30	2.40	2.40	3.20		
	9	9	18			36	2.00	2.00	4.00		
	9	12	12			33	2.18	2.91	2.91		
	9	12	18			39	1.85	2.46	3.69		
	12	12	12			36	2.67	2.67	2.67		
	INTERNAL UNIT						CAPACITY (KW)				
	Unit A	Unit B	Unit C	Unit D	Unit E	TOTAL UNIT'	Unit A	Unit B	Unit C	Unit D	Unit E
HEATING	9	9				18	2.80	2.80			
	9	12				21	2.74	3.66			
	12	12				24	3.50	3.50			
	9	18				27	2.53	5.07			
	12	18				30	3.04	4.56			
	18	18				36	3.95	3.95			
	9	9	9			27	2.65	2.65	2.65		
	9	9	12			30	2.52	2.52	3.36		
	9	9	18			36	2.10	2.10	4.20		
	9	12	12			33	2.29	3.05	3.05		
	9	12	18			39	1.94	2.58	3.88		
	12	12	12			36	2.80	2.80	2.80		

The specifications in this catalog are subject to change without notice in order for ARYA to bring the latest innovations to its customers. ARYA assumes no responsibility for any errors or omissions.
omissions in this catalog.

multi plus combinations 3-27

TOTAL CATACITY (KW)			TOTAL POWER ABSORBED (KW)			TOTAL ABSORPTION (A)230V			SEER	CLASS ENERGY	EER
Min.	Nom.	Max	Min.	Nom.	Max	Min.	Nom.	Max			
2.80	5.60	6.16	0.30	1.71	1.90	1.45	8.47	9.33	6.10	A++	3.27
2.80	6.40	7.04	0.30	1.95	2.22	1.45	9.41	10.89	6.10	A++	3.28
3.00	7.00	7.72	0.35	2.10	2.22	1.69	10.13	10.89	6.10	A++	3.33
2.80	7.60	8.69	0.35	2.20	2.53	1.69	10.62	12.42	6.10	A++	3.45
3.00	7.60	8.80	0.35	2.25	2.55	1.69	10.86	12.52	6.10	A++	3.38
3.00	7.90	8.80	0.40	2.40	2.60	1.93	11.58	12.77	6.10	A++	3.29
2.80	7.90	8.80	0.35	2.45	2.85	1.69	12.70	2.00 pm	6.10	A++	3.23
2.80	8.00	8.80	0.35	2.47	2.75	1.69	12.84	2.00 pm	6.10	A++	3.24
2.80	8.00	8.80	0.45	2.48	2.85	2.17	12.93	2.00 pm	6.10	A++	3.23
2.80	8.00	8.80	0.40	2.48	2.85	1.93	12.93	2.00 pm	6.10	A++	3.23
2.80	8.00	8.80	0.50	2.48	2.85	2.42	13.12	2.00 pm	6.10	A++	3.23
3.00	8.00	8.80	0.45	2.48	2.85	2.17	13.03	2.00 pm	6.10	A++	3.23
TOTAL CATACITY (KW)			TOTAL POWER ABSORBED (KW)			TOTAL ABSORPTION (A)230V			SCOP	CLASS ENERGY	COP
Min.	Nom.	Max	Min.	Nom.	Max	Min.	Nom.	Max			
2.80	5.60	6.16	0.35	1.40	1.90	1.59	7.21	9.33	4.00	A+	3.99
2.80	6.40	7.04	0.35	1.56	2.22	1.59	8.01	10.89	4.00	A+	4.10
3.00	7.00	7.72	0.40	1.68	2.22	1.81	8.62	10.89	4.00	A+	4.17
2.80	7.60	8.69	0.42	1.76	2.53	1.90	9.03	12.43	4.00	A+	4.32
3.00	7.60	8.80	0.42	1.80	2.55	1.90	9.24	12.53	4.00	A+	4.22
3.00	7.90	8.80	0.45	1.92	2.60	2.04	9.86	12.77	4.00	A+	4.11
2.45	7.96	8.80	0.42	2.15	2.85	1.90	10.90	2.00 pm	4.00	A+	3.71
2.70	8.40	8.80	0.42	2.23	2.85	1.90	11.45	2.00 pm	4.00	A+	3.77
2.70	8.40	8.80	0.45	2.23	2.85	2.04	11.81	2.00 pm	4.00	A+	3.77
2.70	8.40	8.80	0.42	2.23	2.85	1.90	11.81	2.00 pm	4.00	A+	3.77
2.70	8.40	8.80	0.50	2.23	2.85	2.26	12.58	2.00 pm	4.00	A+	3.77
2.70	8.40	8.80	0.45	2.25	2.85	2.04	12.06	2.00 pm	4.00	A+	3.73

The specifications in this catalog are subject to change without notice so that ARYA can bring the latest innovations to its customers. ARYA assumes no responsibility for any errors or omissions in this catalog.

multi plus combinations 4-32

	INTERNAL UNIT						CAPACITY (KW)				
	Unit A	Unit B	Unit C	Unit D	Unit E	TOTAL UNIT'	Unit A	Unit B	Unit C	Unit D	Unit E
COOLING	9	9				18	2.70	2.70			
	9	12				21	2.49	3.31			
	12	12				24	3.30	3.30			
	9	18				27	2.47	4.93			
	12	18				30	3.12	4.68			
	18	18				36	4.00	4.00			
	9	9	9			27	2.87	2.87	2.87		
	9	9	12			30	2.58	2.58	3.44		
	9	9	18			36	2.25	2.25	4.50		
	9	12	12			33	2.45	3.27	3.27		
	9	12	18			39	2.17	2.89	4.34		
	12	12	12			36	3.13	3.13	3.13		
	12	12	18			42	2.69	2.69	4.03		
	9	9	9	9		36	2.35	2.35	2.35	2.35	
	9	9	9	12		39	2.17	2.17	2.17	2.89	
	9	9	9	18		45	1.96	1.96	1.96	3.92	
	9	9	12	12		42	2.10	2.10	2.80	2.80	
	9	12	12	12		45	1.96	2.61	2.61	2.61	
	INTERNAL UNIT						CAPACITY (KW)				
	Unit A	Unit B	Unit C	Unit D	Unit E	TOTAL UNIT'	Unit A	Unit B	Unit C	Unit D	Unit E
HEATING	9	9				18	2.80	2.80			
	9	12				21	2.70	3.60			
	12	12				24	3.50	3.50			
	9	18				27	2.70	5.40			
	12	18				30	3.40	5.10			
	18	18				36	4.25	4.25			
	9	9	9			27	2.70	2.70	2.70		
	9	9	12			30	2.63	2.63	3.50		
	9	9	18			36	2.35	2.35	4.70		
	9	12	12			33	2.55	3.40	3.40		
	9	12	18			39	2.17	2.89	4.34		
	12	12	12			36	3.12	3.12	3.12		
	12	12	18			42	2.69	2.69	4.03		
	9	9	9	9		36	2.36	2.36	2.36	2.36	
	9	9	9	12		39	2.18	2.18	2.18	2.91	
	9	9	9	18		45	2.00	2.00	2.00	4.00	
	9	9	12	12		42	2.14	2.14	2.86	2.86	
	9	12	12	12		45	2.00	2.67	2.67	2.67	

The specifications in this catalog are subject to change without notice in order for ARYA to bring the latest innovations to its customers. ARYA assumes no responsibility for any errors or omissions.
omissions in this catalog.

ABBINAMENTI multi plus combinations 4-32

TOTAL CATACITY (KW)			TOTAL POWER ABSORBED (KW)			TOTAL ABSORPTION (A)230V			SEER	CLASS ENERGY	EER
Min.	Nom.	Max	Min.	Nom.	Max	Min.	Nom.	Max			
2.80	5.40	6.16	0.37	1.56	1.80	1.62	7.93	8.74	6.10	A++	3.47
2.80	5.80	7.04	0.37	1.65	1.90	1.62	8.42	9.23	6.10	A++	3.52
3.00	6.60	7.70	0.40	1.85	1.95	1.76	9.44	9.47	6.10	A++	3.57
2.80	7.40	8.80	0.37	2.05	2.10	1.62	10.46	10.20	6.10	A++	3.61
3.00	7.80	9.57	0.40	2.15	2.25	1.76	10.97	10.93	6.10	A++	3.63
3.00	8.00	9.57	0.42	2.20	2.25	1.84	11.22	10.93	6.10	A++	3.64
2.80	8.60	9.65	0.37	2.65	2.86	1.62	13.52	13.89	6.10	A++	3.25
2.80	8.60	9.65	0.37	2.65	2.86	1.62	13.52	13.89	6.10	A++	3.25
2.80	9.00	9.65	0.37	2.75	2.86	1.62	14.03	13.89	6.10	A++	3.27
2.80	9.00	9.65	0.37	2.75	2.86	1.62	14.03	13.89	6.10	A++	3.27
2.80	9.40	9.65	0.37	2.80	2.95	1.62	14.28	14.33	6.10	A++	3.36
3.00	9.40	9.65	0.40	2.80	2.86	1.76	14.28	13.89	6.10	A++	3.36
3.00	9.40	9.65	0.40	2.80	2.95	1.76	14.28	14.33	6.10	A++	3.36
3.10	9.40	10.20	0.41	2.77	3.50	1.80	14.10	5.00 pm	6.10	A++	3.40
3.10	9.40	10.20	0.41	2.78	3.50	1.80	14.18	5.00 pm	6.10	A++	3.38
3.10	9.80	10.40	0.50	3.00	3.50	2.20	3.30pm	5.00 pm	6.10	A++	3.27
3.10	9.80	10.20	0.45	3.00	3.50	1.98	3.30pm	5.00 pm	6.10	A++	3.27
3.10	9.80	10.40	0.50	3.00	3.50	2.20	3.30pm	5.00 pm	6.10	A++	3.27

TOTAL CATACITY (KW)			TOTAL POWER ABSORBED (KW)			TOTAL ABSORPTION (A)230V			SCOP	CLASS ENERGY	COP
Min.	Nom.	Max	Min.	Nom.	Max	Min.	Nom.	Max			
2.55	5.60	6.16	0.37	1.48	1.77	2.30	7.54	8.61	4.00	A+	3.79
2.55	6.30	7.04	0.37	1.57	1.88	2.30	8.00	9.14	4.00	A+	4.02
2.55	7.00	7.70	0.37	1.76	2.11	2.48	8.97	10.25	4.00	A+	3.98
2.55	8.10	8.80	0.37	1.95	2.34	2.30	9.94	11.35	4.00	A+	4.16
2.55	8.50	9.57	0.37	2.04	2.45	2.48	10.42	11.91	4.00	A+	4.16
2.55	8.50	9.80	0.37	2.09	2.51	2.61	10.67	12.18	4.00	A+	4.07
2.55	8.10	9.24	0.37	2.13	2.96	2.30	12.60	2.40pm	4.00	A+	3.80
2.55	8.75	10.01	0.37	2.23	3.08	2.30	13.09	14.95	4.00	A+	3.92
2.55	9.40	10.20	0.37	2.35	3.19	2.30	13.57	5.00 pm	4.00	A+	4.00
2.55	9.35	10.20	0.37	2.34	3.14	2.30	13.33	5.00 pm	4.00	A+	4.00
2.80	9.40	10.20	0.40	2.46	3.36	2.30	2.30pm	5.00 pm	4.00	A+	3.82
2.55	9.35	10.20	0.37	2.46	3.19	2.48	13.57	5.00 pm	4.00	A+	3.80
2.80	9.40	10.20	0.40	2.50	3.42	2.48	14.54	5.00 pm	4.00	A+	3.76
2.80	9.45	10.20	0.40	2.55	3.50	2.48	1.00 pm	5.00 pm	4.00	A+	3.71
2.80	9.45	10.20	0.40	2.55	3.50	2.48	1.00 pm	5.00 pm	4.00	A+	3.71
2.80	10.00	10.40	0.40	2.65	3.50	2.48	13.70	5.00 pm	4.00	A+	3.77
2.80	10.00	10.40	0.40	2.65	3.50	2.48	14.70	5.00 pm	4.00	A+	3.77
2.80	10.00	10.40	0.40	2.65	3.50	2.48	15.70	5.00 pm	4.00	A+	3.77

The specifications in this catalog are subject to change without notice so that ARYA can bring the latest innovations to its customers. ARYA assumes no responsibility for any errors or omissions in this catalog.

multi plus combinations 5-42

	INTERNAL UNIT						CAPACITY (KW)				
	Unit A	Unit B	Unit C	Unit D	Unit E	TOTAL UNIT'	Unit A	Unit B	Unit C	Unit D	Unit E
COOLING	9	9				18	3.00	3.00			
	9	12				21	2.83	3.77			
	12	12				24	3.60	3.60			
	9	18				27	2.67	5.33			
	12	18				30	3.48	5.22			
	18	18				36	4.90	4.90			
	9	9	9			27	3.00	3.00	3.00		
	9	9	12			30	2.70	2.70	3.60		
	9	9	18			36	2.63	2.63	5.25		
	9	12	12			33	2.73	3.64	3.64		
	9	12	18			39	2.54	3.38	5.08		
	12	12	12			36	3.50	3.50	3.50		
	12	12	18			42	3.29	3.29	4.93		
	12	18	18			48	2.88	4.31	4.31		
	18	18	18			54	3.83	3.83	3.83		
	9	9	9	9		36	2.63	2.63	2.63	2.63	
	9	9	9	12		39	2.42	2.42	2.42	3.23	
	9	9	9	18		45	2.20	2.20	2.20	4.40	
	9	9	12	12		42	2.36	2.36	3.14	3.14	
	9	9	12	18		48	2.06	2.06	2.75	4.13	
	9	12	12	12		45	2.20	2.93	2.93	2.93	
	9	12	12	18		51	2.03	2.71	2.71	4.06	
	9	12	18	18		57	1.82	2.42	3.63	3.63	
	9	18	18	18		63	1.71	3.43	3.43	3.43	
	12	12	12	12		48	2.88	2.88	2.88	2.88	
	12	12	12	18		54	2.56	2.56	2.56	3.83	
	12	12	18	18		60	2.40	2.40	3.60	3.60	
	9	9	9	9	9	45	2.44	2.44	2.44	2.44	2.44
	9	9	9	9	12	48	2.29	2.29	2.29	2.29	3.05
	9	9	9	9	18	54	2.08	2.08	2.08	2.08	4.17
	9	9	9	12	12	51	2.21	2.21	2.21	2.94	2.94
	9	9	9	12	18	57	1.97	1.97	1.97	2.63	3.95
	9	9	9	18	18	63	1.86	1.86	1.86	3.71	3.71
	9	9	12	12	12	54	2.08	2.08	2.78	2.78	2.78
	9	9	12	12	18	60	1.95	1.95	2.60	2.60	3.90
	9	12	12	12	12	57	1.97	2.63	2.63	2.63	2.63
	9	12	12	12	18	63	1.86	2.48	2.48	2.48	3.71
	12	12	12	12	12	60	2.60	2.60	2.60	2.60	2.60

The specifications in this catalog are subject to change without notice in order for ARYA to bring the latest innovations to its customers. ARYA assumes no responsibility for any errors or omissions.
omissions in this catalog.

ABBINAMENTI multi plus combinations 5-42

TOTAL CATACITY (KW)			TOTAL POWER ABSORBED (KW)			TOTAL ABSORPTION (A)230V			SEER	CLASS ENERGY	EER
Min.	Nom.	Max	Min.	Nom.	Max	Min.	Nom.	Max			
2.80	6.00	6.60	0.38	1.55	2.02	1.67	6.84	8.96	6.10	A++	3.87
2.80	6.60	7.26	0.38	1.65	2.14	1.67	7.25	9.51	6.10	A++	4.01
3.00	7.20	7.92	0.40	1.85	2.40	1.75	8.13	10.66	6.10	A++	3.90
2.80	8.00	8.80	0.38	2.04	2.66	1.67	9.01	11.81	6.10	A++	3.91
3.00	8.70	9.57	0.40	2.14	2.79	1.75	9.45	12.39	6.10	A++	4.06
3.00	9.80	10.50	0.42	2.19	2.85	1.84	9.67	12.68	6.10	A++	4.47
2.80	9.00	9.90	0.45	2.59	3.37	1.97	11.43	14.98	6.10	A++	3.47
2.80	9.00	10.45	0.45	2.65	3.45	1.97	11.68	15.31	6.10	A++	3.40
2.80	10.50	12.32	0.45	2.70	3.51	1.97	11.90	15.60	6.10	A++	3.89
2.80	10.00	11.00	0.45	2.78	3.61	1.97	12.25	16.06	6.10	A++	3.60
2.80	11.00	12.65	0.45	2.85	3.71	1.97	12.56	16.46	6.10	A++	3.86
3.00	10.50	11.55	0.45	2.94	3.82	1.97	12.96	16.98	6.10	A++	3.57
3.30	11.50	12.76	0.70	2.99	3.89	3.07	13.19	17.29	6.10	A++	3.84
3.30	11.50	12.98	0.75	3.05	3.97	3.29	13.44	17.62	6.10	A++	3.77
3.30	11.50	13.10	0.80	3.10	4.03	3.51	13.66	17.91	6.10	A++	3.71
2.80	10.50	12.32	0.55	3.30	4.29	2.41	14.54	19.06	6.10	A++	3.18
2.80	10.50	13.09	0.55	3.32	4.32	2.41	14.63	19.18	6.10	A++	3.16
3.30	11.00	13.10	0.65	3.38	4.39	2.85	14.90	19.53	6.10	A++	3.25
3.30	11.00	13.10	0.65	3.42	4.45	2.85	15.07	19.76	6.10	A++	3.22
3.30	11.00	13.10	0.65	3.46	4.50	2.85	15.25	19.99	6.10	A++	3.18
3.30	11.00	13.10	0.65	3.48	4.52	2.85	15.34	20.10	6.10	A++	3.16
3.50	11.50	13.50	0.70	3.50	4.55	3.07	15.43	20.22	6.10	A++	3.29
3.50	11.50	13.50	0.70	3.60	4.68	3.07	15.87	20.80	6.10	A++	3.19
4.00	12.00	13.50	0.75	3.65	4.75	3.29	16.09	21.09	6.10	A++	3.29
3.50	11.50	13.10	0.65	3.68	4.78	2.85	16.22	21.26	6.10	A++	3.13
3.50	11.50	13.50	0.65	3.58	4.65	2.85	15.78	20.68	6.10	A++	3.21
4.00	12.00	13.50	0.75	3.62	4.71	3.29	15.95	20.91	6.10	A++	3.31
3.30	12.20	13.10	0.73	3.81	5.40	3.20	16.80	24.00	6.10	A++	3.20
3.30	12.20	13.10	0.73	3.81	5.40	3.20	16.80	24.00	6.10	A++	3.20
3.50	12.50	13.50	0.75	3.92	5.40	3.29	17.28	24.00	6.10	A++	3.19
3.50	12.50	13.50	0.75	3.96	5.40	3.29	5.45pm	24.00	6.10	A++	3.16
3.50	12.50	13.50	0.75	4.00	5.40	3.29	17.63	24.00	6.10	A++	3.13
4.00	1.00 pm	13.50	0.80	4.20	5.40	3.51	18.51	24.00	6.10	A++	3.10
3.50	12.50	13.50	0.75	3.95	5.40	3.29	17.41	24.00	6.10	A++	3.16
4.00	1.00 pm	13.50	0.80	4.10	5.40	3.51	18.07	24.00	6.10	A++	3.17
3.50	12.50	13.50	0.75	4.05	5.40	3.29	17.85	24.00	6.10	A++	3.09
4.00	1.00 pm	13.50	0.80	4.20	5.40	3.51	18.51	24.00	6.10	A++	3.10
4.00	1.00 pm	13.50	0.80	4.15	5.40	3.51	18.29	23.97	6.10	A++	3.13

The specifications in this catalog are subject to change without notice so that ARYA can bring the latest innovations to its customers. ARYA assumes no responsibility for any errors or omissions in this catalog.

multi plus combinations 5-42

	INTERNAL UNIT						CAPACITY (KW)				
	Unit A	Unit B	Unit C	Unit D	Unit E	TOTAL UNIT'	Unit A	Unit B	Unit C	Unit D	Unit E
HEATING	9	9				18	3.00	3.00			
	9	12				21	2.83	3.77			
	12	12				24	3.60	3.60			
	9	18				27	2.67	5.33			
	12	18				30	3.48	5.22			
	18	18				36	4.90	4.90			
	9	9	9			27	3.00	3.00	3.00		
	9	9	12			30	2.70	2.70	3.60		
	9	9	18			36	2.63	2.63	5.25		
	9	12	12			33	2.73	3.64	3.64		
	9	12	18			39	2.54	3.38	5.08		
	12	12	12			36	3.50	3.50	3.50		
	12	12	18			42	3.29	3.29	4.93		
	12	18	18			48	2.88	4.31	4.31		
	18	18	18			54	3.83	3.83	3.83		
	9	9	9	9		36	2.63	2.63	2.63	2.63	
	9	9	9	12		39	2.42	2.42	2.42	3.23	
	9	9	9	18		45	2.20	2.20	2.20	4.40	
	9	9	12	12		42	2.36	2.36	3.14	3.14	
	9	9	12	18		48	2.06	2.06	2.75	4.13	
	9	12	12	12		45	2.20	2.93	2.93	2.93	
	9	12	12	18		51	2.03	2.71	2.71	4.06	
	9	12	18	18		57	1.82	2.42	3.63	3.63	
	9	18	18	18		63	1.71	3.43	3.43	3.43	
	12	12	12	12		48	2.88	2.88	2.88	2.88	
	12	12	12	18		54	2.56	2.56	2.56	3.83	
	12	12	18	18		60	2.40	2.40	3.60	3.60	
	9	9	9	9	9	45	2.44	2.44	2.44	2.44	2.44
	9	9	9	9	12	48	2.29	2.29	2.29	2.29	3.05
	9	9	9	9	18	54	2.08	2.08	2.08	2.08	4.17
	9	9	9	12	12	51	2.21	2.21	2.21	2.94	2.94
	9	9	9	12	18	57	1.97	1.97	1.97	2.63	3.95
	9	9	9	18	18	63	1.86	1.86	1.86	3.71	3.71
	9	9	12	12	12	54	2.08	2.08	2.78	2.78	2.78
	9	9	12	12	18	60	1.95	1.95	2.60	2.60	3.90
	9	12	12	12	12	57	1.97	2.63	2.63	2.63	2.63
	9	12	12	12	18	63	1.86	2.48	2.48	2.48	3.71
	12	12	12	12	12	60	2.60	2.60	2.60	2.60	2.60

The specifications in this catalog are subject to change without notice in order for ARYA to bring the latest innovations to its customers. ARYA assumes no responsibility for any errors or omissions.
omissions in this catalog.

multi plus combinations 5-42

TOTAL CATACITY (KW)			TOTAL POWER ABSORBED (KW)			TOTAL ABSORPTION (A)230V			SCOP	CLASS ENERGY	COP
Min.	Nom.	Max	Min.	Nom.	Max	Min.	Nom.	Max			
3.00	6.00	6.60	0.38	1.40	2.02	1.66	5.99	8.96	4.00	A+	4.30
3.00	6.60	7.26	0.38	1.48	2.27	1.66	6.35	10.08	4.00	A+	4.46
3.20	7.20	7.92	0.40	1.66	2.53	1.75	7.12	11.24	4.00	A+	4.34
3.00	8.00	8.80	0.38	1.84	2.72	1.66	7.89	12.10	4.00	A+	4.35
3.20	8.70	9.57	0.40	1.93	2.79	1.75	8.28	12.39	4.00	A+	4.51
3.00	9.80	11.44	0.42	1.98	2.85	1.84	8.47	12.68	4.00	A+	4.96
3.00	9.00	9.90	0.38	2.33	3.37	1.66	10.01	14.98	4.00	A+	3.86
3.00	9.00	10.45	0.38	2.39	3.45	1.66	10.23	15.31	4.00	A+	3.77
3.00	10.50	12.32	0.38	2.43	3.51	1.66	10.42	15.60	4.00	A+	4.32
3.00	10.00	11.00	0.38	2.50	3.61	1.66	10.73	16.06	4.00	A+	4.00
3.00	11.00	12.65	0.38	2.57	3.71	1.66	11.00	16.46	4.00	A+	4.29
3.20	10.50	11.55	0.40	2.65	3.82	1.75	11.35	16.98	4.00	A+	3.97
3.50	11.50	12.76	0.40	2.69	3.89	1.75	11.55	17.29	4.00	A+	4.27
3.50	11.50	12.98	0.40	2.75	3.97	1.75	11.77	17.62	4.00	A+	4.19
3.50	11.50	13.50	0.42	2.79	4.03	1.84	11.96	17.91	4.00	A+	4.12
3.00	10.50	12.32	0.38	2.97	4.29	1.66	12.73	19.06	4.00	A+	3.54
3.00	10.50	13.09	0.38	2.99	4.32	1.66	12.81	19.18	4.00	A+	3.51
3.30	11.00	13.10	0.38	3.04	4.39	1.66	13.04	19.53	4.00	A+	3.62
3.30	11.00	13.10	0.38	3.08	4.45	1.66	13.20	19.76	4.00	A+	3.57
3.30	11.00	13.50	0.38	3.11	4.50	1.66	13.35	19.99	4.00	A+	3.53
3.30	11.00	13.10	0.38	3.13	4.52	1.66	13.43	20.10	4.00	A+	3.51
3.70	11.50	13.50	0.38	3.15	4.55	1.66	13.51	20.22	4.00	A+	3.65
3.70	11.50	13.50	0.38	3.24	4.68	1.66	13.89	20.80	4.00	A+	3.55
4.20	12.00	13.50	0.38	3.29	4.75	1.66	14.09	21.09	4.00	A+	3.65
3.30	11.50	13.10	0.40	3.31	4.78	1.75	2.20pm	21.26	4.00	A+	3.47
3.70	11.50	13.50	0.40	3.22	4.65	1.75	13.82	20.68	4.00	A+	3.57
4.20	12.00	13.10	0.40	3.26	4.71	1.75	13.97	20.91	4.00	A+	3.68
3.30	12.20	13.10	0.80	3.69	5.40	3.50	15.80	24.00	4.00	A+	3.31
3.50	12.20	13.10	0.80	3.69	5.40	3.50	15.80	24.00	4.00	A+	3.31
3.70	12.50	13.50	0.85	3.75	5.40	3.71	16.08	24.00	4.00	A+	3.33
3.70	12.50	13.50	0.85	3.75	5.40	3.71	16.08	24.00	4.00	A+	3.33
3.70	12.50	13.50	0.90	3.80	5.40	3.93	16.29	24.00	4.00	A+	3.29
4.20	1.00 pm	13.50	0.95	3.80	5.40	4.15	16.29	24.00	4.00	A+	3.42
3.70	12.50	13.50	0.85	3.75	5.40	3.71	16.08	24.00	4.00	A+	3.33
4.20	1.00 pm	13.50	0.90	3.80	5.40	3.93	16.29	24.00	4.00	A+	3.42
3.70	12.50	13.50	0.90	3.80	5.40	3.93	16.29	24.00	4.00	A+	3.29
4.20	1.00 pm	13.50	0.90	3.80	5.40	3.93	16.29	24.00	4.00	A+	3.42
4.20	1.00 pm	13.50	0.90	3.80	5.40	3.93	16.29	23.97	4.00	A+	3.42

The specifications in this catalog are subject to change without notice so that ARYA can bring the latest innovations to its customers. ARYA assumes no responsibility for any errors or omissions in this catalog.