

TECHNICAL DATA	3.5KW SINGLE-PHASE	11KW TrIFASE	22KW TrIFASE
INPUT VOLTAGE	AC 230V	AC 230V	AC 230V
OUTPUT VOLTAGE	400V	400V	400V
INPUT FREQUENCY	47-63Hz	47-63Hz	47-63Hz
MAXIMUM OUTPUT POWER	3.5 kW (single-phase)	11 kW (three-phase)	22 kW (three-phase)
MAXIMUM OUTPUT CURRENT	32A	32A	32A
TYPE OF INTERFACE	IEC 62196-2, SAEJ1772	IEC 62196-2, SAEJ1772	IEC 62196-2, SAEJ1772
DIMENSIONS (L/L/P)	295x195x65 mm	295x195x65 mm	295x195x65 mm
WEIGHT	6kg	8kg	8kg
LCD SCREEN	3.5" colour display	3.5" colour display	3.5" colour display
RCD	Type A+6	Type A+6	Type A+6
LED INDICATOR	yes	yes	yes
CURRENT REGULATION	yes	yes	yes
ROOM TEMPERATURE	-40°C-+75°C	-40°C-+75°C	-40°C-+75°C
RELATIVE HUMIDITY	0-95% non-condensing	0-95% non-condensing	0-95% non-condensing
MAXIMUM ALTITUDE	<2000m	<2000m	<2000m
COOLING	natural air	natural air	natural air
STANDBY POWER CONSUMPTION	<8 W	<8 W	<8 W
DEGREE OF PROTECTION IP	IP66	IP66	IP66

TECHNICAL DATA	7KW SINGLE-PHASE
NOMINAL VOLTAGE	220V~240V AC
RATED CURRENT	32A
FREQUENCY	50/60Hz
OUTPUT VOLTAGE	220V~240V AC
MAXIMUM CURRENT	32A
MAXIMUM POWER	7kW
CHARGING CONNECTOR	Type 2 cable or type 2 socket
CABLE LENGTH	5m
LED LIGHT	Green / Yellow / Red
RFID READER	Mifare ISO/EC 14443A (Max 5)
EXTERNAL COMMUNICATION	Wi-Fi 2.4G / Bluetooth
IP LEVEL	IP65
TEMPERATURE	-30° C- +50°C
HUMIDITY	5%~95%
ALTITUDE	<2000m
DIMENSIONS	315*163*92 mm (H*W*D)
PACKAGE DIMENSIONS	434*324*210mm (L*W*H)
WEIGHT	4.5