





TECHNICAL DATA	AR150L	AR300L
GROSS AREA	1.905m <sup>2</sup>	1.905m <sup>2</sup> *2
DIMENSIONS	2140x890x226mm	2140 (*2)x890x226mm
EMPTY WEIGHT	42kgs	42kgs*2
CAPACITIES	150L	150L
MAX. OPERATING TEMPERATURE	85°C	85°C
MAX. OPERATING PRESSURE	4 bar	4 bar
ELECTRICAL RESISTANCE	1.5KW	1.5KW
CONNECTIONS	2x3/4" F	2x3/4" F
INSTALLATION	Flat roof/ pitched roof	Flat roof/ pitched roof
USERS		

TECHNICAL DATA	AR200L	AR400L
GROSS AREA	2.499m <sup>2</sup>	2.499m <sup>2</sup> *2
DIMENSIONS	2100x1190x220mm	2100 (*2)x1190x220mm
EMPTY WEIGHT	60kgs	60kgs*2
CAPACITIES	200L	400L
MAX. OPERATING TEMPERATURE	85°C	85°C
MAX. OPERATING PRESSURE	4 bar	4 bar
ELECTRICAL RESISTANCE	1.5KW	1.5KW
CONNECTIONS	2x3/4" F	2x3/4" F
INSTALLATION	Flat roof/ pitched roof	Flat roof/ pitched roof
USERS		

**THERMAL PERFORMANCE**

